




# CORROSION RESISTANT PRODUCTS

## 440C STAINLESS STEEL BALL BEARINGS - Metric Sizes

| Part Number | Boundary Dimensions - mm |     |    |
|-------------|--------------------------|-----|----|
|             | d                        | D   | B  |
| S608-2RS    | 8                        | 22  | 7  |
| S627-2RS    | 7                        | 22  | 7  |
| S6000-2RS   | 10                       | 26  | 8  |
| S6001-2RS   | 12                       | 28  | 8  |
| S6002-2RS   | 15                       | 32  | 9  |
| S6003-2RS   | 17                       | 35  | 10 |
| S6004-2RS   | 20                       | 42  | 12 |
| S6005-2RS   | 25                       | 47  | 12 |
| S6006-2RS   | 30                       | 55  | 13 |
| S6007-2RS   | 35                       | 62  | 14 |
| S6008-2RS   | 40                       | 68  | 15 |
| S6009-2RS   | 45                       | 85  | 16 |
| S6200-2RS   | 10                       | 30  | 9  |
| S6201-2RS   | 12                       | 32  | 10 |
| S6202-2RS   | 15                       | 35  | 11 |
| S6203-2RS   | 17                       | 40  | 12 |
| S6204-2RS   | 20                       | 47  | 14 |
| S6205-2RS   | 25                       | 52  | 15 |
| S6206-2RS   | 30                       | 62  | 16 |
| S6207-2RS   | 35                       | 72  | 17 |
| S6208-2RS   | 40                       | 80  | 18 |
| S6209-2RS   | 45                       | 85  | 19 |
| S6210-2RS   | 50                       | 90  | 20 |
| S6300-2RS   | 10                       | 35  | 11 |
| S6303-2RS   | 15                       | 47  | 14 |
| S6304-2RS   | 20                       | 52  | 15 |
| S6305-2RS   | 25                       | 62  | 17 |
| S6306-2RS   | 30                       | 72  | 19 |
| S6307-2RS   | 35                       | 80  | 21 |
| S6308-2RS   | 40                       | 90  | 23 |
| S6309-2RS   | 45                       | 100 | 25 |
| S6904-2RS   | 20                       | 37  | 9  |
| S6905-2RS   | 25                       | 42  | 9  |
| S6910-2RS   | 50                       | 72  | 12 |



2RS  
with double  
non contact seals

Apply these bearings in a variety of services where they may be subjected to moisture, corrosive and abrasive atmospheres.