




AGRICULTURAL BEARINGS



DISC HARROW BALL BEARINGS TRIPLE LIP SEAL Series Relubricatable type



ROUND BORE														
Unit No.	Type	Bore d		Outside Diameter D	tolerance +0.000" to minus		Ring Width +0.000,-0.005 +0.00,-12 mm		Static Load Rating Cor		Dynamic Load Rating Cr		Weight	
		In. mm	In. mm		In. mm	In. mm	B Inner	C Outer	lbf	N	lbf	N	Lbs	kg
GW209PPB4	4	1.5350 39.00	0.0100 0.250	3.3465 85	0.0006 0.015	1.188 30.18	1.188 30.18	4 550	20 200	8 300	36 800	1.65	0.748	
GW209PPB2	4	1.7717 45.00	0.0005 0.013	3.3465 85	0.0006 0.015	1.188 30.18	1.188 30.18	4 550	20 200	8 300	36 800	1.44	0.653	
GW209PPB11	2	1.7810 45.24	0.0100 0.250	3.3465 85	0.0006 0.015	1.438 36.53	0.866 22.00	4 550	20 200	8 300	36 800	1.37	0.621	
GW210PPB2	4	1.9380 49.23	0.0005 0.013	3.5433 90	0.0006 0.015	1.188 30.18	1.188 30.18	5 200	23 000	9 000	39 900	1.5	0.680	
GW211PPB13	2	1.7850 45.34	0.0100 0.250	3.9370 100	0.0006 0.015	1.312 33.34	0.984 25.00	6 550	29 000	11 000	48 800	2.02	0.916	
GW211PPB10	4	1.9380 49.23	0.0006 0.015	3.9370 100	0.0006 0.015	1.312 33.34	1.312 33.34	6 550	29 000	11 000	48 800	2.26	1.025	
GW214PPB3	4	1.9380 49.23	0.0006 0.015	4.9213 125	0.0008 0.020	1.562 39.69	1.562 39.69	9 800	43 500	16 000	71 000	4.85	2.200	
GW211PPB2	4	2.1880 55.58	0.0006 0.015	3.9370 100	0.0006 0.015	1.312 33.34	1.312 33.34	6 550	29 000	11 000	48 800	2.62	1.188	
GW211PPB9	2	2.1950 55.75	0.0070 0.180	3.9370 100	0.0006 0.015	1.562 39.69	0.984 25.00	6 550	29 000	11 000	48 800	2.02	0.916	
GW214PPB6	2	2.6881 68.28	0.0006 0.015	4.9213 125	0.0008 0.020	2.688 68.26	1.102 28.00	9 800	43 500	16 000	71 000	4.75	2.155	
GW214PPB2	4	2.7559 70.00	0.0006 0.015	4.9213 125	0.0008 0.020	1.562 39.69	1.562 39.69	9 800	43 500	16 000	71 000	3.96	1.796	