




AGRICULTURAL BEARINGS



DISC HARROW BALL BEARINGS TRIPLE LIP SEAL Series Relubricatable type



Type 3

| SQUARE BORE | | | | | | | | | | | | | |
|-------------|------|------------|------|--------------------|----------------------------|---------------------------------------|----------------|------------------------|--------|------------------------|--------|--------|-------|
| Unit No. | Type | Shaft Size | | Outside Diameter D | tolerance +0.000" to minus | Ring Width +0.000,-0.005 +0.00,-12 mm | | Static Load Rating Cor | | Dynamic Load Rating Cr | | Weight | |
| | | | | | | B Inner | C Outer | | | | | | |
| | | In. | mm | In. mm | In. mm | In. mm | In. mm | lbf | N | lbf | N | Lbs | kg |
| GW208PP17 | 3 | 1-1/8 | 28.6 | 3.3755 85.738 | 0.0005 0.013 | 1.438 36.53 | 1.188 30.18 | 4 500 | 19 900 | 8 300 | 36 800 | 2.04 | 0.925 |
| | | | | | | | | | | | | | |
| GW211PP3 | 3 | 1-1/2 | 38.1 | 3.9370 100 | 0.0006 0.015 | 1.312 33.34 | 1.312 33.34 | 6 550 | 29 000 | 11 000 | 48 800 | 2.79 | 1.266 |
| GW211PP17 | 3 | 1-1/2 | 38.1 | 3.9370 100 | 0.0006 0.015 | 1.75 44.45 | 1.312 33.34 | 6 550 | 29 000 | 11 000 | 48 800 | 2.62 | 1.188 |