


BEARING UNITS




TRIANGLE FLANGE UNITS - Ductile Iron SARFT 200 Series

Normal Duty Eccentric Collar Locking Square Bolt Holes







| Unit No. | | Shaft Dia. | | Dimensions inch / mm | | | | | | | | | | | | Bearing | Housing | Weight Lbs |
|----------|---------------|------------|----|------------------------|-----------------------|---------------------|---------------------|---------------------------|---------------------|-------------------|---------------------|-------------------|------------------|----------------------|--------------------------|------------------|---------|---------------------|
| | | | | а | е | i | b | d | g | s | z | L | n | w | Size | No. | No. | kg |
| SARFT | 204 204-12 | 3/4 | 20 | 3-9/16 90.5 | 2-13/16 71.4 | 7/16 11.1 | 2-13/64 56.0 | 1-3/4 44.5 | 7/16 11.1 | 11/32 8.7 | 1-3/8 34.9 | 1.220 31.0 | 0.276 7.0 | 1-1/4 31.8 | 5/16 <i>M8</i> | SA 204 204-12 | RFT204 | 0.81 0.37 |
| SARFT | 205 | | 25 | | | | | | | | | | | | | SA 205 | | 1.06 0.48 |
| | 205-14 | 7/8 | | 3-3/4 | 3 | 7/16 | 2-13/16 | 1-7/8 | 1/2 | 11/32 | 1-23/64 | 1.220 | 0.295 | 1-1/2 | 5/16 | 205-14 | | |
| | 205-15 | 15/16 | | 95.3 | 76.2 | 11.1 | 71.4 | 47.6 | 12.7 | 8.7 | 34.5 | 31.0 | 7.5 | 38.1 | M8 | 205-15 | | |
| | 205-16 | 1 | | | | | | | | | | | | | | 205-16 | | |
| SARFT | 206 | | 30 | | | | | | | | | | | | | SA 206 | RFT206 | 1.54 0.70 |
| | 206-17 | 1-1/16 | | | | | 3 76.2 | 2-9/32 <i>57.9</i> | 19/32 15.1 | 13/32 10.3 | 1-17/32 38.9 | 1.406 35.7 | 0.315 8.0 | 1-3/4 44.5 | 3/8 M10 | 206-17 | | |
| | 206-18 | 1-1/8 | | 4-9/16 115.9 | 3-9/16 90.5 | 7/16 11.1 | | | | | | | | | | 206-18 | | |
| | 206-19 | 1-3/16 | | 113.5 | 50.5 | 11.1 | | | | | | | | | | 206-19 | | |
| | 206-20 | 1-1/4S | | | | | | | | | | | | | | 206-20 | | |
| SARFT | 207 | | 35 | | | | | | | | | | | | | SA 207 | RFT207 | 2.00 0.91 |
| | 207-20 | 1-1/4 | | 4 12/16 | 3-15/16 | 1/2 | 2-15/22 | 2-12/22 | 10/22 | 12/22 | 1-45/64 | 1 521 | 0.335 | 2-3/16 | | 207-20 | | |
| | 207-21 | | | 122.2 | 100.0 | 1/2 12.7 | 88.1 | 2-13/32 61.1 | 19/32 15.1 | 13/32 10.3 | 43.3 | 1.531 38.9 | 8.5 | 55.6 | | 207-21 | | |
| | 207-22 | 1-3/8 | | | | | | | | | | | | | | 207-22 | | |
| | 207-23 | 1-7/16 | | | | | | | | | | | | | l | 207-23 | | |