




# NARROW INNER RING BEARINGS



## CSA 200 Series - Cylindrical OD

Normal Duty  
Eccentric Collar Locking



Cylindrical O. D.

Unit No.	Shaft Dia.		Dimensions inch / mm									Basic load Ratings lbf / N		Weight kg Lbs	
			D	L	Bi	Be	n	Di	K	G	ds	dynamic C	static Co		
	In.	mm													
CSA 201-8 202 202-10	1/2	15	1.575	1.126	3/4	15/32	0.236	1-3/16	17/32	0.157	M6x1.0	2160	990	0.12	0.26
	5/8		40.0	28.6	19.1	11.9	6.0	30.2	13.5	4.0	1/4-28UNF	9600	4400	0.11	0.24
CSA 204 204-12	3/4	20	1.850	1.220	27/32	9/16	0.276	1-19/64	17/32	0.197	M6x1.0	2900	1460	0.17	0.37
			47.0	31.0	21.5	14.3	7.0	33.0	13.5	5.0	1/4-28UNF	12890	6490	0.16	0.35
CSA 205 205-14 205-15 205-16	7/8	25	2.047	1.220	27/32	19/32	0.295	1-1/2	17/32	0.197	M6x1.0	3150	1700	0.20	0.44
	15/16		52.0	31.0	21.5	15.1	7.5	38.0	13.5	5.0	1/4-28UNF	14000	7560	0.22	0.48
														0.21	0.46
	1													0.19	0.42
CSA 206 206-17 206-18 206-19 206-20	1-1/16	30	2.441	1.406	15/16	5/8	0.315	1-3/4	5/8	0.236	M6x1.0	4390	2510	0.31	0.68
	1-1/8		62.0	35.7	23.8	15.9	8.0	44.5	15.9	6.0	1/4-28UNF	19510	11160	0.33	0.73
	1-3/16													0.33	0.73
	1-3/16													0.30	0.66
	1-1/4S													0.28	0.62
CSA 207 207-20 207-21 207-22 207-23	1-1/4	35	2.835	1.531	1	21/32	0.335	2-3/16	11/16	0.276	M8x1.0	5770	3450	0.49	1.08
	1-5/16		72.0	38.9	25.4	16.7	8.5	55.5	17.5	7.0	5/16-24UNF	25650	15340	0.52	1.14
	1-3/8													0.50	1.10
	1-7/16													0.47	1.03
														0.45	0.99
CSA 208 208-24	1-1/2	40	3.149	1.719	1-3/16	23/32	0.354	2-3/8	23/32	0.276	M8x1.0	6500	3850	0.66	1.45
			80.0	43.7	30.2	18.3	9.0	60.3	18.3	7.0	5/16-24UNF	28890	17110	0.64	1.41
CSA 209 209-26 209-27 209-28	1-5/8	45	3.346	1.719	1-3/16	3/4	0.375	2-1/2	23/32	0.276	M8x1.0	7350	4100	0.65	1.43
	1-11/16		85.0	43.7	30.2	19.1	9.5	63.5	18.3	7.0	5/16-24UNF	32670	18220	0.76	1.67
	1-3/4													0.73	1.61
														0.70	1.54
CSA 210 210-30 210-31 210-32	1-7/8	50	3.543	1.719	1-3/16	25/32	0.394	2-3/4	23/32	0.276	M10x1.25	7900	4690	0.70	1.54
	1-15/16		90.0	43.7	30.2	19.8	10.0	69.8	18.3	7.0	3/8-24UNF	35120	20850	0.83	1.83
	2S													0.79	1.74
														0.74	1.63
CSA 211-35	2-3/16		3.937	1.906	1-9/32	15/16	0.472	3	13/16	0.315	M10x1.25	9750	5850	0.81	1.78
			100.0	48.4	32.5	23.8	12.0	76.2	20.6	8.0	3/8-24UNF	43340	26000		