


## **BEARING UNITS**



RUBBER CARTRIDGES - Cylindrical OD - Vibration Damping

Normal Duty Eccentric Collar Locking





## **RCSM**

\* Also Available with Set Screw Locking in 200 Series Part Numbers. Add Suffix "S" to Part Number. Example - RCSM-12S assembled with Bearing No. CSB204-12 instead of CSA204-12.

Unit No.	Shaft Dia.	Dimensions (mm)								Bearing No.	Rubber No.	Housing Radial Load Rating	Weight
		D	Α	A1	G	м	d1	S1	т	bearing No.	Rubbei No.	<b>Lbf</b> <i>N</i>	Lbs kg
	In.												
RCSM SERIES													
RCSM-8	1/2	<b>2-17/32</b> 64.3	<b>1</b> 25.4	-	-	<b>1-3/8</b> 34.9	<b>1-1/8</b> 28.6	<b>7/8</b> 22.2	<b>1/2</b> 12.7	CSA 201-8	RCSM 40/65	<b>200</b> 880	<b>0.87/</b> 0.395
RCSM-10	5/8									CSA 202-10			<b>0.85/</b> 0.386
RCSM-12	3/4	<b>2-17/32</b> 64.3	<b>1</b> 25.4	-	-	<b>1-9/16</b> 39.7	<b>1-5/16</b> 33.3	<b>59/64</b> 23.4	<b>1/2</b> 12.7	CSA 204-12	RCSM 47/65	<b>250</b> 1120	<b>1.04/</b> 0.472
RCSM-14	7/8									CSA 205-14			<b>1.19/</b> 0.540
RCSM-15	15/16	<b>2-17/32</b> 64.3	<b>1</b> 25.4	-	-	<b>1-25/32</b> 45.2	<b>1-1/2</b> 38.1	<b>59/64</b> 23.4	<b>1/2</b> 12.7	CSA 205-15	RCSM 52/65	<b>300</b> 1340	<b>1.17/</b> 0.531
RCSM-16	1									CSA 205-16			<b>1.13/</b> 0.513
RCSM-17	1-1/16	<b>3-3/32</b> 78.6	1-3/16 30.2	-	-	<b>1-7/8</b> <i>47.6</i>	<b>1-3/4</b> 44.4	1-3/32 27.7	<b>19/32</b> 15.1	CSA 206-17	RCSM 62/79	<b>300</b> 1340	<b>1.76/</b> 0.798
RCSM-18	1-1/8									CSA 206-18			<b>1.76/</b> 0.798
RCSM-19	1-3/16									CSA 206-19			<b>1.69/</b> 0.767
RCSM-20	1-1/4S									CSA 206-20			<b>1.65/</b> 0.748
		<ul> <li>+ RCSM Series part numbers are complete assemblies.</li> <li>+ Cylindrical OD insert bearing mounted in rubber cushion.</li> <li>+ Static conductive rubber cushion dampens vibrations.</li> <li>+ Standard Part Number is eccentric collar locking type.</li> </ul>											